



URGENT

ROUTINE


MANDATORY

INFORMATIONAL

Service Bulletin

DATE May 15, 1974

NUMBER 2908 40001

<p>ATTENTION: SERVICE MANAGERS AND OWNERS</p>	<p>GROUP</p> <p style="text-align: center;">8</p>																								
<p>In order to provide an improved ride in the FMC 2900R Motor Home, the tire pressure can be reduced from the previously specified 75 psi. The schedule below should be followed in establishing the tire pressures you use.</p>	<p>SUBJECT</p>																								
<table style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="text-align: center; border-bottom: 1px solid black;">FRONT AXLE WEIGHT (LBS)</th> <th style="text-align: center; border-bottom: 1px solid black;">FRONT TIRE PRESSURE (PSI)</th> <th style="text-align: center; border-bottom: 1px solid black;">REAR AXLE WEIGHT (LBS)</th> <th style="text-align: center; border-bottom: 1px solid black;">REAR TIRE PRESSURE (PSI)</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">4300</td> <td style="text-align: center;">50</td> <td style="text-align: center;">7960</td> <td style="text-align: center;">50</td> </tr> <tr> <td style="text-align: center;">4650</td> <td style="text-align: center;">55</td> <td style="text-align: center;">8640</td> <td style="text-align: center;">55</td> </tr> <tr> <td style="text-align: center; border: 1px solid black;">5000</td> <td style="text-align: center; border: 1px solid black;">60</td> <td style="text-align: center;">9340</td> <td style="text-align: center;">60</td> </tr> <tr> <td style="text-align: center;">5335</td> <td style="text-align: center;">65</td> <td style="text-align: center; border: 1px solid black;">10,090</td> <td style="text-align: center; border: 1px solid black;">65</td> </tr> <tr> <td style="text-align: center;">5510</td> <td style="text-align: center;">70</td> <td style="text-align: center;">10,480</td> <td style="text-align: center;">70</td> </tr> </tbody> </table>	FRONT AXLE WEIGHT (LBS)	FRONT TIRE PRESSURE (PSI)	REAR AXLE WEIGHT (LBS)	REAR TIRE PRESSURE (PSI)	4300	50	7960	50	4650	55	8640	55	5000	60	9340	60	5335	65	10,090	65	5510	70	10,480	70	<p>TIRE PRESSURES</p>
FRONT AXLE WEIGHT (LBS)	FRONT TIRE PRESSURE (PSI)	REAR AXLE WEIGHT (LBS)	REAR TIRE PRESSURE (PSI)																						
4300	50	7960	50																						
4650	55	8640	55																						
5000	60	9340	60																						
5335	65	10,090	65																						
5510	70	10,480	70																						
<p>The enclosed blocks indicate the tire pressures recommended by the Michelin Company for the FMC 2900R. If you operate your vehicle at axle weights less than those specified in the enclosed blocks, then the tire pressures can be further reduced accordingly.</p> <p>For long distance, high-speed travel with a fully loaded vehicle, it is recommended that the 60 psi in front tires and 65 psi in rear tires be increased by 10 percent.</p>	<p>MODEL (S) AFFECTED</p> <p style="text-align: center;">2900R</p> <p style="text-align: center;">MOTOR HOME</p>																								
<p style="text-align: center;">  JOHN L. STREVER Service Manager </p>	<p>(Factory Use Only) Information added to:</p> <p>OWNER MANUAL (S)</p> <hr/> <p>SERVICE MANUAL (S)</p> <hr/> <p>PARTS MANUAL (S)</p> <hr/> <p>WARRANTY MANUAL (S)</p> <hr/> <p>OTHER</p>																								